

### OPERATING INFORMATION

#### FAIL-SAFE EXITING

To meet life-safety codes, standard Securitech control trim allows exiting at all times with the simple depression of the lever. In MAGLATCH models, power is interrupted to the electromagnet (which instantly releases it) as the lever is depressed and the latch is retracted.

#### FAIL-SECURE ENTRY

The exterior lever is rigid unless released by key or electric signal. Loss of power keeps the lever in the locked mode, unless released by key. The exterior lever is locked whenever the key is removed.

#### CLASSROOM FUNCTION

In certain cases, the exterior lever is to remain unlocked for extended periods. By ordering the "CF" function, rotation of the key unlocks the lever. The key may be removed and the lever remains unlocked until the key is re-inserted and rotated to re-lock the lever. The latch always projects to maintain the fire-rating.

#### STAIRWELL RE-ENTRY

Certain building codes require locked exterior levers to automatically unlock upon a signal from the fire-alarm system or loss of power. Securitech control trim with "RE" designation meets this requirements and does not require special frame preparation.

#### Heavy Duty Latch Lock Bodies




**AML:** Standard mortise lock body (1-1/4"x8" ANSI door prep) supplied.

**MML:** Mini-mortise lock body (3" lock case depth) for medium-stile doors (1-1/4"x6-7/8" faceplate)

**NSL:** Narrow-stile lock body for use on 2" tube aluminum doors and iron gates, 1-1/4"x6-7/8" faceplate

**ASL:** Same as NSL, but with Adams-Rite size faceplate (1"x6-7/8")

Select the right size lock body to suit your door style. All lock bodies feature heavy-duty deadlatching bolts. "AML" designated locksets are fire-rated.



Standard size strike supplied with all models (non-electric)



#### ELECTROLATCH & MAGLATCH MODELS INCLUDE:

Most popular model, office applications	9010-GG-DC-630	For use with all access control systems
Stairwell re-entry, fire alarm interface, access control interface	9010-GG-RE-630	Meets life-safety requirements
Intercom-release, medium size apartment building	9010-UG-AC-676	Door "buzzes" when released
Electromagnetic lock control, access control release, office use	9020-GG-DC-630	Electromagnetic lock by others
Heavy-traffic area, electromagnetic lock control, intercom released	9030-UG-AC-676	Ideal for public housing & universities
Narrow-stile aluminum door, intercom release, new or retrofit	CFL-10-DC-676	Easy-to-install, replaces broken strikes

From apartment buildings to offices to community centers and many other doors, Securitech Electric Control Trim will meet your most demanding electric locking needs.



#### Additional Products



**Securitech has many other solutions including ARTE Signal trim to replace request-to-exit buttons on doors without exterior electric release trim**



**SECURITECH GROUP, INC.**

54-45 44TH STREET MASPETH, NY 11378 (800) 622-LOCK

(718) 392-9000

FAX: (718) 392-8944

www.securitech.com