

Apartment Building

CFL-10-AC: will sound an audible "buzz" when intercom button is pressed.

Iron Gate

Coordinate lock series based upon lock box provided by gate fabricator.

Access Control System

Use "DC" release for silent operation. Card power supply can be used.

Retail Store

Use "CD" to allow door to be push/pull while store is open.

Hollow Metal Door

CFL-14 will fit into standard mortise opening.

Replace Electric Strike

Filler plate (by others) might be needed to reduce to 4-7/8"

Custom Application

Contact factory with your special requirements.

Standard Operation

Enter By Key: Insert key, rotate, pull handle down to enter.
 Removing key instantly re-locks the lever.

Enter By Buzz: Pull lever down while unit is buzzing (AC)

Enter By LED: Pull lever down when LED from Access Control system turns green (DC)

Exiting: Exit by pulling down inside lever at all times

Applications:

- Apartment Building Entrances
- Narrow-Stile Doors With Access Control Systems
- Gates


CF Classroom Function


The exterior cylinder is used to unlock the lever for extended periods. A key is not required for entry until the lever is re-locked by key. On models with electric release, the electric release will function while the lever is locked.

Applications:

- Classrooms
- Office Entry
- Fire-Rated Applications*

* requires fire-rated mortise lockset (CFL-15)

CD Cylinder Dogging


The interior lever is locked in the downward position which keeps the latch retracted. The door can then be pushed or pulled open. The lever is released and the door re-locked by use of key. Exiting is possible at all times, regardless of mode.


Applications:

- High-Traffic Storefront Entry
- Public Arena
- Parks
- Museum
- Educational Institutions

Lock Bodies


ASL
fits "Adams-Rite" type faceplate
1"x6-7/8"

for 2" tube


NSL
1-1/4"x 6-7/8" faceplate



MML
1-1/4"x 6-7/8" faceplate

for 3-1/4" medium stile tube

FML
1-1/4"x 8" faceplate



AML
1-1/4" x 8" faceplate
ANSI type, Fire-Rated Lockset

for wide-stile tube or regular door

4-7/8" Stainless Steel Strike
Supplied With All Models

How To Order

A) Series With Lock Type:

CFL-10	ASL
CFL-11	NSL
CFL-12	MML
CFL-13	FML
CFL-14	AML

Mortise cylinder required for all exterior trims (cylinder by others)

B) Electric Info & Operation

Electric Release:

- AC "AC" : Standard electric release requires 24vAC,30va power. Fail-Secure exterior operation.
- DC "DC" : 24vDC electric release option.
- RE Re-Entry function. Requires continuous 24vDC to remain locked. Exterior becomes Fail-Safe with loss of power.

Special Non-Electric Model:

- ME Key unlock only. Does not contain solenoid

Special Functions:

- CF Clasroom function. Exterior lever remains unlocked until relocked by key.
- CD Push/Pull operation. Interior lever is locked in open position. Latch does not project until lever is unlocked by interior key.

C) Finish:

676 Standard finish is powder coated black. Custom finish available. Contact factory.

See Electrolatch For Trims With Architectural Finishes

D) Handing:

LH, RH, LHR, RHR

Trims are not field reversible. Lock bodies may be reversed. Strikes are handed.

Sample Model#:
CFL-10-AC-676-RHR