

EASY MODEL NUMBER CREATOR

ALL AUTO-BOLT & P*E*D*S MODELS BEGIN WITH "8"

NUMBER OF DEADBOLTS
 1= SINGLE POINT 3= 3 POINT LOCKING
 2= 2 POINT LOCKING 4= 3 MOVING & FIXED BOLT ON HINGE SIDE
 2V_ = 2 POINT VERTICAL

INTERIOR TYPE
(C=Cross Bar)

EXTERIOR TRIM TYPE
(See Below)

8 3 C 47 - GG - AC - SBO - 630 - LHR

EXT. TRIM STYLE
(For Lever Models)

ELECTRIC RELEASE TYPE
(For Electric Lever Models)

SPECIAL FEATURES:
 Surface-Bolt Option, Hurricane Doors, Top Trigger, Keyed Dogging, Cylinder Dogging

FINISH:
 Lever Models: (Int. & Ext.)
 Panic Bar: (Ext. Finish)

DOOR SWING:
 Auto-Bolt Locks Are Handed-Use LH, LHR, RH Or RHR

Designate "F" after Trim# for Fire-Rated Models Omit fields not required for specific trims when creating model number



EXTERIOR OPTIONS					
LEVER TRIM #44 Lever Handle #47 With Electric Release UG Or GG Styles	 #41 Passage Lever Handle	PULL TRIM #12 Pull Handle No Cylinder (Use With KDM)	 #13 Pull Handle	 #24 Pull Handle Securi-Guard	 #28 Knurled Aluminum Pull Plate Securiguard
EXIT ONLY #11 No Exterior Trim No Cylinder	DIGITAL KEYPAD #55DX2 Lever Handle Digital Keypad Entry & Lockout #55DX3 With Electric Release	PUSHBUTTON #55PB Lever Handle Pushbutton Entry #56PB With Electric Release	SECURIGUARD #26 Lever Handle Securi-Guard #95 With Electric Release	THUMBTURN #18 Thumb-Turn	GG Trim available for #44, 47 & 41 models.

CUSTOM FUNCTIONS & MODELS AVAILABLE: CONTACT THE FACTORY WITH YOUR SPECIAL NEEDS

Additional Ordering Information:

Finishes: UG: 676 (Powder Coat Black) GG: 626 or 605. All interior panic bars are stainless steel.
 Mortise Cylinders For Exterior Trim: Min. 1-1/8" Required. Cylinders & cams are not furnished by Securitech.
 Cam Info: Standard Function - Cloverleaf (Corbin wing-type). Classroom Function - Short Adams-Rite type.
 Cam For #55 & #56 Models (DX & PB): Straight Yale type.
 Cylinders for Pull Handle & Pull Plate models require special "Gear Cam" provided by Securitech.
 Removable-core or special high-security cylinders should be sent to Securitech for "Gear Cam" mounting.
 Specify door thicknesses if other than 1-3/4". Specify door width and height.
 Notify factory if using removable core cylinder when ordering "UG" trim for special cylinder protector.
 Electric release available in 24vAC or 24vDC. AC models require 30va transformer or power supply.
 All Securitech MP Alarms are available for use with P*E*D*S exit devices.

TOP TRIGGER MODELS A special top trigger (in place of the trigger below the horizontal deadbolt) is available for use on doors with multi-point locking which are openly exposed to the general public and where there is a high likelihood of mis-use (such as rear exit doors in public housing). This is also used on pairs of doors.	EDGE PLATES Doors which have inverted U-channels do not require special edge preparations, as they will use the elevated edge plate which fits into the channel. A flat edge plate is available for wood doors or flush HM doors.	VANDAL-RESISTANCE "Slip-Clutch" Lever Handle Standard With UG & GG Lever Will "Breakaway" If Forced, But Does Not Unlock Door. Lever Can Be Simply Reset By Lifting Back To Original (Horizontal) Position. Hardened Steel Cylinder Protectors On Both Units	"Slip-Off" Pull Handle: Spoils Attempts To Rip The Door From The Frame By Tying A Chain To The Lever And Pulling With A Car. Pull Handle Will Separate From Guard Plate If Forced.
--	--	--	--